## MOUNTAIN VIEW CENTER FOR THE PERFORMING ARTS

## SECONDSTAGE

## TECHNICAL SPECIFICATIONS

Seating Capacity Maximum seating is 212.

The standard configuration is a thrust stage set-up, seating between 158 and

212.

Options (at extra cost) include:

• Cabaret tables and chairs.

• "In the round" floor seating.

Other riser configurations that comply with fire codes may be approved

when the facility is contracted.

Stage 54'-3" x 58'-6" Octagonally shaped "black box" theater.

Usable stage approx. 17'-0" x 28'-0" (standard seating.)

Grid Height 18′ – 5″ to top surface of grid. Grid thickness is variable.

Stage Floor Sprung stage floor with stained and sealed particleboard surface, painted

black.

Loading Dock Dock is at ground level via curving driveway at street level.

(1) truck capacity.

Loading Door 12'-0" H x 7'-4" W into 13'-0" x 24'-0" dock area (ground level)

Stage Access Up 6'-9" W x 9'-9" H ramped corridor, through 6'-10" wide doors.

Client Access There are (2) doors for client access. Both have keypads on them. One is at

the loading dock and the other is sub-level in the parking garage.

Parking of any vehicles in loading dock area must be approved four (4)

weeks prior to event.

Parking in garage below facility is free.

Film & Video Equipment Closed circuit color monitor system feeds to lobbies, green room and

rehearsal studio.

(1) Front Projection Screen, 12' x 12', motorized.

## **INVENTORY**

Use of any Center equipment is subject to availability.

Soft Goods Black Legs to be used as needed in following quantities and sizes:

(8) 12'-0" W x 18'-0" H (8) 9'-0" W x 18'-0" H (2) 21'-0" W x 17'-0" H

Traveler track to accept the 17'-0" H, materials

Sound Equipment Allen and Heath ML4000 – 24A mixer (Specifications available upon

request).

(2) Otari 5050B II 1/4-inch reel-to-reel tape decks (available by pre-

arrangement).

(1) Tascam 102 Mark II cassette decks.(1) Tascam CC-222 Cassette/ CD player.(1) Yamaha SPX 990 Sound processor.

(3) Mackie SRM450 speakers (central cluster).

(4) Shure wireless microphone system, with lavalieres. (Please see the

Facility Fee Schedule for wireless system rates)

Telex FM assistive listening system.

(5) Mic stands.(5) Microphones.

(1) 100' 8 channel snake, no returns.

All necessary cable.

Intercom System Clear-com intercom system.

(5) single-muff headsets.

(10) intercom jacks throughout theater.

(5) single channel belt packs.

All necessary cables.

Staging Wenger Versalite platform system in 4'-0" x 8'-0" and 4'-0" x 6'-0" sections,

variable height from 0'-6" to 4'-0" (in 6" increments).

Acoustic Shell Wenger Roll-Away Shell, 11 pieces

Choral Risers Wenger 3-step risers, 12 pieces

Lighting Control ETC Express 48/96 - 2-scene preset (48 channels and 24 sub masters.) Also

has 96-channel memory control

Dimming capacity is 96 Strand CD-80 dimmers (2.4Kw)

(3) 2.4 Kw non-dims (swappable with dimmers)

(4) 20 amp non-dims (permanent) House plug style is 3- pin stage plug

Assorted length cables

(10) two-fers

Lighting Instruments - (Confirm equipment needs with Technical Services Manager during advance meeting)

#	SIZE	TYPE	WATTS
22	6 x 12	Altman ERS	750
22	6 x 9	Altman ERS	750
22	6"	Altman Fresnel	500
10	PAR64	VN, N, MFL, WFL	1KW
2	L&E	Mini Follow Spots	600

<sup>\*\*</sup>Some additional lighting equipment may be available.\*\*